

## Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Drew Zande (USA)	Lexmark
Internet site *	www.lexmark.ted / www.lexmark.com	
Additional information		

	pased on product specification or test results based obtained from sample testing), that the product ts given in this declaration.
Type of product *	Multi Function Mono Laser Printer
Commercial name *	Lexmark MX710de, Lexmark MX710de 3, Lexmark MX710dhe, Lexmark XM5163, Lexmark MX717de
Model number *	MX710de, MX710de 3, MX710dhe, XM5163, MX717de
Issue date *	February 28, 2014 (Revised June 1, 2017)
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	MX710de, MX710de 3, MX710dhe, XM5163, MX717de		
Issue date *	February 28, 2014 (Revised June 1, 2017	Logo	Lexmark

Product	environmental attributes - Legal requirements	Require	ment	t met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent			
	chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference).  Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	X		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	$\boxtimes$		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS),	$\overline{}$	$\overline{}$	X
	Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).  Comment: Legal reference has no maximum concentration values.		Ш	
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split		$\Box$	$\boxtimes$
	aromatic amines. (See legal reference and Note B1)			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as			$\boxtimes$
	pentachlorophenol and derivatives (see legal reference).			
D / 01	Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5	$\boxtimes$		Ш
	microgram/cm²/week (see legal reference).			
P1.10*	Comment: Max limit in legal reference when tested according to EN1811:1998.  REACH Article 33 information about substances in articles is available at (add URL or mail contact):		$\overline{}$	_
P1.10	REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains	$\boxtimes$		
	more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be			
	marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or	$\boxtimes$		
P2.3*	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)  Batteries and accumulators are easily removable by either users or service providers (as dependent on the			
F2.3	design of the product). Exception: Batteries that are permanently installed for safety, performance, medica		Ш	Ш
	or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).			$\overline{}$
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal		₩	╬
	reference).		<u> </u>	
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).		Ш	
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	$\boxtimes$		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	$\boxtimes$	$\Box$	
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the	X	Ħ	$\overline{}$
	product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	l 🖂		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	$\boxtimes$	$\Box$	
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea		旹	Ħ
. 0.0	Protocol (see legal reference).  Comment: Legal reference has no maximum concentration values.		Ш	

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	MX710de, MX710de 3, MX710dhe, XM5163, MX717de		
Issue date *	February 28, 2014 (Revised June 1, 2017)	Logo	Lexmark

Product environmental attributes - Market requirements - Environmental conscious design	Require	men	met
Item *=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6 Treatment information			
P6.1* Information for recyclers/treatment facilities is available (see legal reference).	$\boxtimes$		
P7 Design			
Disassembly, recycling P7.1* Parts that have to be treated separately are easily separable			
P7.2* Plastic materials in covers/housing have no surface coating.		$\overline{H}$	+
P7.3* Plastic parts >100g consist of one material or of easily separable materials.			$\vdash$
P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.		H	∺
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available too		H	∺
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).		H	∺
Product lifetime			
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives		П	
P7.8* Upgrading can be done using commonly available tools		Ħ	Ħ
P7.9. Spare parts are available after end of production for: <b>5</b> years			Ħ
P7.10 Service is available after end of production for: 5 years			
Material and substance requirements			
P7.11* Product cover/housing material type:			
Material type: ABS Material type: HIPS Material type: PC/A	ABS		
P7.12 Electrical cable insulation materials of power cables are PVC free.		$\boxtimes$	
P7.13 Electrical cable insulation materials of signal cables are PVC free		$\boxtimes$	
P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.		$\boxtimes$	
P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21.	(See	$\boxtimes$	
Note B2)			
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:		Ш	
P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components):			
TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:		ш	ш
restriction in the second of t			
Alt. 2		_	_
Chemical specifications of flame retardants in printed circuit boards (without components) >25g accord	ling 🔀		
ISO 1043-4: <i>FR(16)</i> P7.18 Alt. 1			
P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparation	ns in $\square$		
concentrations above 0.1%:		ш	ш
Comment: No legal limits exist, this is a market requirement.			
1. Chemical name: , CAS #:			
2. Chemical name: , CAS #: 3. Chemical name: , CAS #:			
Alt. 2			
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:			
FR(40), FR(17), FR(16), FR(50)		Щ	Щ.
P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R4 R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	5,	Ш	
P7.20 Of total plastic parts' weight >25g, recycled material content is <i>up to 33</i> %.			
P7.21 Of total plastic parts' weight >25g, biobased material content is %.			
P7.22 Light sources are free from mercury			
If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries mg			
P8.1* Battery chemical composition: <i>Lithium Manganese Dioxide, LiMnO2</i>			
P8.2 Batteries meet the requirements of the following voluntary program/s:			$\dashv$

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	MX710de, MX710de 3, MX710dhe, XM5163, MX717de				
Issue date *	February 28, 2014 (Revised June 1, 2017)	Logo	•	Lexmark	

Product env	rironmental att	ributes - Market re	quirements (con	tinued)		Requiremen	t met
Item						Yes No	n.a.
	nergy consumpti						
9.1 Fo	or the product the	following power levels	or energy consump	tions are report	ted:		
Energy mode *	*	Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC	at	Reference / Standard for energy modes and test method *	'
Copying		854 W	<b>808</b> W	<b>794</b> W		Corporate Standard	
Ready 1 Mode	е	67.3 W	<b>69.8</b> W	<b>65.4</b> W		Energy Star I E V2.0	
Ready 2 Mode	е	<b>46.4</b> W	<b>46.6</b> W	46.2 W		Energy Star I E V2.0	
Sleep Mode		<b>2.4</b> W	2.3 W	<b>2.4</b> W		Energy Star I E V2.0	
Hibernate Mo	de	<i>0.51</i> W	<i>0.53</i> W	<b>0.63</b> W		IEC 62301	
Off Mode		0.0 W	<b>0.0</b> W	<b>0.0</b> W		IEC 62301	
EPS No-load		W	W	W			$\boxtimes$
(External power charger plugger outlet but discouther product.)	ed in the wall						
PTEC * Typical Energy	y Consumption	W	W	W			
TEC * Typical Energy	y Consumption	4.6 kWh/week	4.8 kWh/week	5.0 kWh/week		Energy Star I E V2.0	
ETEC * Annual Energy	/ Consumption	kWh/year	kWh/year	kWh/ye	ar		
Display resolut	tion* : Me	gapixels					
Print Speed *	: 63 Images	s per minute				ISO 24734 (US Letter)	
Default time to	enter energy sav	ve mode: 30 minutes				Energy Star I E V2.0	
		ne energy save functio	•	•			
EN		the energy requiremer rersion: <b>2.0</b> Tier: Prod L <b>-UZ 171</b>			m/s:		
	nissions						
		Declared according to ode description	ISO 9296	Declared	1	Declared A-weighted	
P 10.1	ode ivi	ode description		A-weighted sound power		sound pressure level $L_{p\mathrm{Am}}$ (dB)	
				level $L_{W\!Ad}$ (B)	Ope	rator position Bystander positions	
						or Desk side (only if product is not	t
Idle	A *	Ready		* <b>4.8</b>		operator attended)	<u> </u>
	-	Simplex Monochrom		<sup>*</sup> 7.3		57	$\exists  \exists$
	N	ormal Mode					
Oti		Simplex Monochrom uiet Mode	e Printing,	6.9		53	
Me	easured according	~ <del>_</del>	ECMA-74 (only if not covered	by ECMA-74 wit	:h L <sub>pAn</sub>	m measurement distance m)	
	e product meets	_				am/s: RAL-UZ 122/RAL-	

Model number *	MX710de, MX710de 3, MX710dhe, XM5163, MX717de		
Issue date *	February 28, 2014 (Revised June 1, 2017)	Logo	Lexmark

	environmental attributes - Market requirements (continued)	Require	ment	
Item		Yes	No	<u></u>
item	Chamical amissions from printing products	162	INO	n.
P10.3*	Chemical emissions from printing products  Text porformed according to ECMA 229 (ISO/IEC 29360) standard other specific PAL LIZ 423/PAL LIZ			$\overline{}$
1 10.5	Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ 122/RAL-UZ 171		Ш	ш
P10.4	Typical emission rate (print phase) is (mg/h):			
	Dust <0.7 Ozone <0.06 Styrene <0.15 Benzene <0.04 TVOC 10			
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ 122/RAL-UZ 171 are met for:  Dust Ozone Styrene Benzene TVOC			
	Electromagnetic emissions			
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:			
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	X	П	П
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements o EN12281.	f 🛛		
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	$\square$		
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.		П	X
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.	Ħ	$\overline{\sqcap}$	
P13	Packaging and documentation			
	Product packaging material type(s): Corrugated weight (kg): 4.529 Product packaging material type(s): Polystyrene, expanded weight (kg): 1.337  Steel or tinplate – 0.064 kg High Density Polyethylene – 0.212 kg Low Density Polyethylene, expanded – 0.023 kg Polypropylene – 0.0975 kg Paperboard – 0.528 kg			
P13.2*	Product plastic packaging is free from PVC.	$\square$		$\overline{\Box}$
P13.3*	Specify media for user and product documentation (tick box):			H
1 10.0	Electronic , Paper , Other .			ш
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%			
Rev. P13.5	User and product documentation do not contain chlorine bleached paper			
P14	Additional information (See Note B4)			
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.			
P2.1	The battery contained within this product should be disposed of properly with the product. The product is properly la disposal symbol and instructions for such disposal is listed in the product User's Guide.	beled with	the W	EEE
P.2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by t however, is designed for easy removal by recyclers and service providers.	he custom	er;	
P7.14	A small amount of bromine may be present in covers due to sourcing post consumer recycled content. No bromine w added in the processing of these parts.	as intentio	nally	
P7.20	Per IEEE 1680.2 PCR calculation.			
P9.1	Information provided in P9.1 is for products with serial numbers starting with 746337. Print speed listed is Letter; A4 The following table provides energy data for products prior to serial numbers starting with 746337:	speed is 60	0 ppm.	

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	
Copying	854 W	808 W	<b>794</b> W	Corporate Standard	
Ready 1 Mode	88.9 W	103.7 W	91.1 W	Energy Star I E V1.2	
Ready 2 Mode	<b>52.4</b> W	<b>53.3</b> W	<b>49.3</b> W	Energy Star I E V1.2	
Sleep Mode	12.8 W	12.5 W	12.8 W	Energy Star I E V1.2	
Hibernate Mode	<b>0.51</b> W	0.53 W	0.63 W	IEC 62301	
Off Mode	0.0 W	0.0 W	0.0 W	IEC 62301	
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)	W	W	W		
PTEC * Typical Energy Consumption	W	W	W		
TEC * Typical Energy Consumption	6.8 kWh/week	6.4 kWh/week	6.6 kWh/week	Energy Star I E V1.2	
ETEC * Annual Energy Consumption	kWh/year	kWh/year	kWh/year		
Display resolution* : Me	gapixels				
Print Speed * : 63 Image:	s per minute			Corporate Standard	
Default time to enter energy sa	ve mode: 30 minutes			Energy Star I E V1.2	<del></del>
P9.2* Information about t	he energy save function	on is provided with the	he product.		
	the energy requirement version: 1.2 Tier: 1 Pro L UZ 122				

Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle Lexmark Sweden is connected to REPA and El-kretsen

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19