

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	I DIVA A DIV
Contact information *	Nadia Martin (USA)	LEXMARK
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	ype of product * Multifunction Color Laser Printer			
Commercial name *	exmark XS925de			
Model number *	(S925de			
Issue date *	le date * 12/16/2011			
Intended market *	nded market * 🛛 🔀 Global 📃 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			Requirement met		
Item		Yes	No		
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes			
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀			

Model number *		XS925de				
Issue dat	sue date * 12/16/2011 Logo		LEXMARK			
Product	Product environmental attributes - Legal requirements					
Item			Require Yes	No	n.a.	
P1	Hazardo					
P1.1*	1* Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)					
P1.2*	Products	s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.	\square			
P1.3*	Products hydrobro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum				
P1.4*	concent	ration values. s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated				
	terpheny	/I (PCT) in preparations (see legal reference).				
P1.5*	the chai	s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in n containing at least 48% per mass of chlorine in the SCCP (see legal reference).				
P1.6*	Tris-(azi	Ind leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Int: Legal reference has no maximum concentration values.				
P1.7*	Textile a	and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split c amines. (See legal reference and Note B1)			\square	
P1.8*	Wooden pentach	parts do not contain arsenic and chromium as a wood preservation treatment as well as lorophenol and derivatives (see legal reference). nt: Legal reference has no maximum concentration values.				
P1.9*	Parts wi microgra	th direct and prolonged skin contact do not release nickel in concentrations above 0.5 am/cm ² /week (see legal reference). nt: Max limit in legal reference when tested according to EN1811:1998.				
P1.10*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): <i>Program Manager, H0D9237, 740 W. New Circle Rd., Lexington, KY 40550</i>				
P2	Batterie					
P2.1*	more that marked	oduct contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is I in user manual. (See legal reference)				
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other batteries or lators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on th design of the product). Exception: Batteries that are permanently installed for safety, performance, medic or data integrity reasons do not have to be "easily removable". (See legal reference)					
P3		EMC connection to the telephone network and labeling				
P3.1*		duct complies with legally required safety standards as specified (see legal reference).				
P3.2*	referenc					
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complie with legally required standards for radio and telecommunication devices (see legal reference).					
P3.4*	The pro	duct is labeled to show conformance with applicable legal requirements (see legal reference).	\square			
P4		nable materials				
P4.1*	legal ref	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see erence and Note B1).				
P4.2*		her is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).				
P4.3*	product/	//toner formulation/preparation is classified as hazardous according to applicable regulations, the packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these nents is available (see legal reference).	\square			
P5		t packaging				
P5.1*	hexavale	ng and packaging components do not contain more than 0.01% lead, mercury, cadmium and ent chromium by weight of these together.	1 N			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).					
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montre Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.					

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *		XS925de					
Issue date *		12/16/2011	Logo	LEXM	ARK		
Product	Product environmental attributes - Market requirements - Environmental conscious design Requirement n						
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.		Yes	No	n.a.		
P6	Treatment information						
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).						
P7	Design						
	Disassembly, recycling						
P7.1*	Parts that have to be treated separately are easily separable		\boxtimes				
P7.2*	Plastic materials in covers/housing have no surface coating.			Ē			
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.			H	H	
P7.4*		arts >25g have material codes according to ISO 11469 referring ISO 1043.			╞	⊢⊢	
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly a	wailable tools		╞	<u> </u>	
					<u> </u>	<u> </u>	
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		\square			
	Product						
P7.7*		ng can be done e.g. with processor, memory, cards or drives					
P7.8*	Upgradir	ng can be done using commonly available tools					
P7.9.	Spare pa	arts are available after end of production for: 5 years		-			
P7.10	Service i	s available after end of production for: 5 years					
	Material	and substance requirements					
P7.11*	Product	cover/housing material type:					
	Material	type: PC+ABS Material type: ABS Materia	l type:				
P7.12	Electrica	I cable insulation materials of power cables are PVC free.			\boxtimes		
P7.13	Electrica	I cable insulation materials of signal cables are PVC free			\boxtimes		
P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.		$\overline{\boxtimes}$	Ē		
P7.15		ed circuit boards (without components) >25g are halogen free .as defined in IEC6	1249-2-21. (See			H	
	Note B2						
P7.16	Flame re	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:		\square			
P7.17	Marking: Alt. 1	FR(40)					
F7.17		Il specifications of flame retardants in printed circuit boards >25g (without compone	ents).				
	TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:						
	Alt. 2						
		Il specifications of flame retardants in printed circuit boards (without components) >	25g according				
	ISO 104	3-4:					
P7.18	Alt. 1			_	_	_	
		etarded plastic parts >25g contain the following flame retardant substances	/preparations ir	ı 📘			
		ations above 0.1%:					
		ent: No legal limits exist, this is a market requirement.					
		ical name: , CAS #: ical name: , CAS #:					
		ical name: , CAS #:					
	Alt. 2						
		I specifications of flame retardants in plastic parts >25g according ISO 1043-4:		_	_	_	
P7.19		arts >25g are free from flame retardant substances/ preparations above 0.1% class 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	sified as R45,				
P7.20		plastic parts' weight >25g, recycled material content is %.					
P7.21		plastic parts' weight >25g, biobased material content is %.					
P7.22	Light sources are free from mercury						
		ry is used specify: Number of lamps: and max. mercury content per lamp:	mg				
P8	Batterie						
P8.1*	Battery of	hemical composition: Lithium Manganese Dioxide, LiMnO2					
P8.2	Batteries	meet the requirements of the following voluntary program/s:					

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model nu	mber *	XS925de								
Issue date	te * 12/16/2011 Logo LEXMARK									
Dreduct environmental attributes Market requirements (continued)						tmot				
Item	duct environmental attributes - Market requirements (continued) Requirement met Yes No n.a						n.a.			
P9										
9.1			following power levels	or energy consum	ptions are report	ted:				
Energy mode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC		t Reference / Standard for energ modes and test method *		energy		
Printing		W	640.2 W	612.1 W		Corporate Standard				
Сору			W	715.5 W	640.8 W	640.8 W		Corporate Standard		
Scan			W	138.8 W	144.1 W		Corporate Standard			
Ready Mo	ode		W	127.2 W	119.8 W		Energy Star TEC Test Procedure			
Sleep Mo	de		W	25.5 W	26.4 W		Energy Star TEC Test Procedure			
Off Mode			W	0.002 W	0.015 W		IEC 62301			
EPS No-lo	bad		W	W	W					
(External p charger pl outlet but the produc	ugged in the	ne wall								
PTEC * Typical Energy Consumption		sumption	W	W	W	W				
TEC * Typical Energy Consumption		sumption	kWh/week	7.803 kWh/week	7.758 kWh/we	ek	Energy Star TEC Test Procedure		lure	
ETEC * Annual Energy Consumption		sumption	kWh/year	kWh/year	kWh/year					
Display re	solution*	: Me	l gapixels							
Print Spee	ed *	: 31 Images	s per minute							
Default tim		-	/e mode: 5 minutes							
P9.2*			ne energy save functio	n is provided with t	he product.					
P9.3*	The proc	duct meets	the energy requirement	nts of the following	voluntary program	m/s:				
	ENERG	Y STAR® v	ersion: 1.1 Tier: e Angel (RAL UZ 122	Product category				\mathbf{X}		
P10	Emissio		<u> </u>	100 0000						
P10.1	Noise ei Mode		Declared according to ode description	130 9296	Declared		Declared A-	weighted		
					A-weighted		sound pressure lev	-	B)	
					sound power $I_{\text{OV}}(\mathbf{P})$	One	rator position	Bystander p		-
					level L_{WAd} (B)		Desktop	(only if produ	ct is not	
	Idle * Ready * 3.3		17							
			Duplex Mono Printing, Normal Mode		* 7.1	56				
			Simplex Mono Printi Iode	ng, Normal	7.0	55				
	Measure		g to: 🔀 ISO7779 🗌	ECMA-74 (only if not covered	l by ECMA-74 wit	th Lna	m measurement dist	ance r	n)	1
P10.2		duct meets	the acoustic noise req						,	
	Angel)									

Model number *		XS925de				
Issue date *		12/16/2011 Logo	LEXM	ARK		
Product	Product environmental attributes - Market requirements (continued)				tmet	
Item					n.a.	
	Chemica	al emissions from printing products				
P10.3*	P10.3* Test performed according to ECMA-328 (ISO/IEC 28360) standard , other specify: RAL-UZ-122					
P10.4		mission rate (print phase) is (mg/h):				
	1	Dust 1.4 Ozone BQL Styrene 1.4 Benzene BQL TVOC 13				
P10.5	Chemica	l emission requirements of the following voluntary program/s RAL-UZ-122 are met for:	\square			
		Dust 🛛 Ozone 🖂 Styrene 🔀 Benzene 🖾 TVOC 🔀				
		nagnetic emissions				
P10.6	Compute program	er display meets the requirement for low frequency electromagnetic fields of the following voluntary /s:			\square	
P11		able materials for printing products				
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes			
P11.2*	Paper co EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets the requirements I.	of 🔀			
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\square			
P12	Ergonor	nics for computing products				
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes	
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.			\square	
P13	Packagi	ng and documentation				
P13.1*	Product Product	backaging material type(s): Wood weight (kg): 12.453 backaging material type(s): Corrugated weight (kg): 9.529 backaging material type(s): Polystyrene (PS) weight (kg): 1.984				
	Paper =	0.576 kg nsity Polyethylene (LDPE) = 0.129 kg				
P13.2*	Product	plastic packaging is free from PVC.				
P13.3*		nedia for user and product documentation (tick box):			\dashv	
		c 🔍, Paper 🔍, Other 🗌				
P13.4*		r user and product documentation, please specify contained percentage of post-consumer recycled	b			
	fiber: 0	<i>K</i> o				
P14		al information (See Note B4)				
P1.1		duct uses RoHS exemptions for lead used in small amounts for specific applications.				
P2.1		ery contained within this product should be disposed of properly with the product. The pro with the WEEE disposal symbol and instructions for such disposal is listed in the product U			,	
P2.3		ery contained within this product meets the exception listed. The battery is not intended to er; however, is designed for easy removal by recyclers and service providers.	be remo	ved by	the	
P9.1	31 page	s per minute A4; 30 pages per minute Letter				
P10.4	Mono print test results: Ozone – BQL; Styrene - 0.52 mg/hr; Benzene – BQL; Dust – BQL; and TVOC – 7.4 mg/hr BQL = Below Quantifiable Limits (Benzene < 0.03, Ozone < 0.06, Dust < 0.7)					
	Specific	nal company information and company environmental policy may be found at http://lexmark printer and supply item recycling information for your area may be found at http://lexmark. < Sweden is connected to REPA and El-kretsen) nt	

Annex B of ECMA-370 4th edition, June 2009

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19