



ISO/IEC 19798 Yield Test Report

C935 Ship With Equipment Print Cartridge

Printer C935

Part Numbers of Cartridges

Cyan (C) 21Z0391

Yellow (Y) 21Z0393

Magenta (M) 21Z0392

Black (K) 21Z0390

Lexmark Toner Cartridge Yield Claim:

Average Continuous Composite Color (CMY) Cartridge Yield **12,000** standard pages

Average Continuous Black (K) Cartridge Yield **13,000** standard pages

Declared yield in accordance with ISO/IEC 19798

Tested Cartridge Summary:

90% Lower Confidence

Composite Color (CMY) = 14461 pages

Black = 15280 pages

For questions concerning testing contact:

Lexmark International Inc.

740 West New Circle Rd.

Lexington, Ky. 40550 USA

Attn: Laser Supplies Product Manager

Datum der Tests

17-Sep-2007 19-Sep-2007

Number of cartridges in testing	C= 9	M= 9	Y= 9	K= 9
Qty. of cartridges used in calculation	C= 9	M= 9	Y= 9	K= 9
Type of cartridge	Two piece			
Shake Procedure				
1st shake	No shake			
2nd shake	No shake			
Print mode	Continuous			
Number of printers tested	3			
Media used	Hammermill Tidal MP - 20# - Letter			
Paper feed orientation	Long Edge Feed (LEF)			
Driver version	Lexmark Beta 18			
Operating system	Windows XP Professional			
Application software	Adobe Reader 7.0.9			
Test page version	ISO-IEC 24712 Test suite.pdf (7/18/2006 version)			
Power (off/on) everyday	Y			
Pre-generated file used	Y			
Header / Footer used	Y			
Computer	Dell Optiplex GX280			
Computer RAM and CPU type	512 MB RAM and Pentium 4 2.80GHz			
PC / Printer connection	Network			



ISO/IEC 19798 Yield Test Report

Printer	Color	Cartridge SN	Temperature C / F			Humidity			Cartridge Yield	Cartridge used in Calculation
			Avg	Max	Min	Avg	Max	Min		
0291025	C	TC10588	23 / 73	23 / 74	23 / 73	51	52	49	13215	Y
0291020	C	TC10589	23 / 73	23 / 74	23 / 73	51	52	49	12510	Y
0293023	C	TC10594	23 / 73	23 / 74	21 / 70	51	52	49	14010	Y
0291020	C	TC10597	22 / 72	23 / 74	21 / 70	52	57	50	13120	Y
0291025	C	TC10598	22 / 72	23 / 73	21 / 70	52	57	50	14145	Y
0293023	C	TC10593	23 / 73	23 / 74	22 / 71	55	57	52	14935	Y
0291025	C	TC10603	22 / 72	23 / 74	21 / 69	55	57	53	13890	Y
0291020	C	TC10592	22 / 72	23 / 74	21 / 69	55	57	53	13245	Y
0293023	C	TC10596	22 / 72	23 / 74	21 / 69	54	57	53	14420	Y
0291025	K	TK10627	23 / 73	23 / 74	21 / 70	51	52	49	15595	Y
0291020	K	TK10629	22 / 72	23 / 74	21 / 70	51	52	49	15100	Y
0293023	K	TK10630	23 / 73	23 / 74	21 / 70	51	52	49	15280	Y
0291025	K	TK10636	22 / 72	23 / 73	21 / 69	55	57	52	15965	Y
0291020	K	TK10638	22 / 72	23 / 73	21 / 69	55	57	52	16915	Y
0293023	K	TK10631	22 / 72	23 / 73	21 / 69	55	57	52	15420	Y
0291025	K	TK10639	23 / 73	23 / 74	22 / 72	54	55	53	15585	Y
0291020	K	TK10634	23 / 73	23 / 74	23 / 73	54	55	52	16295	Y
0293023	K	TK10633	23 / 73	23 / 74	22 / 72	54	55	54	14890	Y
0291025	M	TM10457	22 / 72	23 / 74	21 / 70	51	52	49	15795	Y
0291020	M	TM10453	23 / 73	23 / 74	23 / 73	51	52	49	14055	Y
0293023	M	TM10548	22 / 72	23 / 74	21 / 70	51	52	49	15605	Y
0291020	M	TM10581	22 / 72	23 / 73	21 / 70	52	57	50	14320	Y
0291025	M	TM10576	22 / 72	23 / 73	21 / 69	55	57	53	15345	Y
0293023	M	TM10466	22 / 72	23 / 73	21 / 69	55	57	52	15760	Y
0291020	M	TM10462	22 / 72	23 / 74	21 / 69	55	57	53	14790	Y
0291025	M	TM10572	23 / 73	23 / 74	23 / 73	54	55	53	15355	Y
0293023	M	TM10577	23 / 73	23 / 74	22 / 72	54	55	53	15520	Y
0291025	Y	TY10572	23 / 73	23 / 74	21 / 70	51	52	49	15510	Y
0291020	Y	TY10573	23 / 73	23 / 74	21 / 70	51	52	49	14925	Y
0293023	Y	TY10579	22 / 72	23 / 74	21 / 70	51	52	49	16760	Y
0291025	Y	TY10583	22 / 72	23 / 73	21 / 69	55	57	52	16765	Y
0291020	Y	TY10578	23 / 73	23 / 74	22 / 71	55	57	52	15200	Y
0293023	Y	TY10576	22 / 72	23 / 73	21 / 69	55	57	53	16495	Y
0291020	Y	TY10577	22 / 72	23 / 74	21 / 69	54	57	53	15600	Y
0291025	Y	TY10580	23 / 73	23 / 74	22 / 72	54	55	53	15965	Y
0293023	Y	TY10582	23 / 73	23 / 74	22 / 72	54	55	53	16590	Y

	Average	Std Dev. Of Sample	90% Lower Confidence
Cyan Cartridge	13721	755	13253
Magenta Cartridge	15172	635	14778
Yellow Cartridge	15979	703	15543
CMY Composite			14461
Black Cartridge	15672	631	15280