



ISO/IEC 19752 Yield Test Report

E250d, E250dn Ship With Equipment Print Cartridge

Printer: E250d, E250dn

Part Numbers: SWE

Declaration of Yield:	Average Cartridge Yield	1500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 2379
Std Dev 124
90% Lower Confidence 2302

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start stop
 5-Jul-2006 7-Jul-2006

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	E250dn G9
Operating system	Window XP
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
		Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS061531A33	6203HG2	71	22	72	22	70	21	59	60	59	2,410	Yes
CAS061531A3D	6203HGD	71	22	72	22	70	21	59	60	59	2,450	Yes
CAS061531A43	6203HH0	71	22	72	22	70	21	59	60	59	2,180	Yes
CAS061531A0A	6203HG2	71	22	72	22	71	21	59	60	57	2,480	Yes
CAS061531A17	6203HGD	71	22	72	22	71	21	59	60	57	2,450	Yes
CAS061531A18	6203HH0	71	22	72	22	71	21	59	60	57	2,190	Yes
CAS061531A4B	6203HG2	72	22	73	23	72	22	50	53	46	2,399	Yes
CAS061531AF0	6203HGD	72	22	73	23	72	22	50	53	46	2,530	Yes
CAS061531A1B	6203HH0	72	22	73	23	72	22	50	53	46	2,319	Yes

Comments and or exceptions: