



ISO/IEC 19752 Yield Test Report

E260 1.0k Ship With

Printer: E260

Declaration of Yield: Average Cartridge Yield 1000 standard pages Declared yield value in accordance with ISO/IEC 19752

Average 1255
Std Dev 87
90% Lower Confidence 1201

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 31-Jul-2008 stop 31-Jul-2008

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure 1st shake 2nd shake
Print mode
Number of printers tested 3
Media used Tidal Hammermill - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version Long Bow Lexmark G9
Operating system Windows XP SP2
Application software Acrobat version 7.0.0
Test page version 19752_Test_Chart_Ver200406.pdf

Table with columns: Cartridge, Printer, Temperature (Avg, Max, Min in F and C), Humidity (Avg, Max, Min), Cartridge Yield, Cartridge used in Calculation. Rows include various cartridge models like CAS0819704ED, CAS0819704F3, etc.

Comments and or exceptions: