



E321/E323 High Yield Print Cartridge
Printer: E321/E323

Declaration of Yield: Average Cartridge Yield 6000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average 7517
Std Dev 486
90% Lower Confidence 7265

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 2-Dec-2004 stop 4-Dec-2004

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake 2nd shake
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 8.2.2
Operating system Windows 2000
Application software Adobe Acrobat version 6.01
Test page version IS_19752_Testpage_Ver.200406.pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Rows include various CAD042002040, CAD042002019, CAD042248483, etc.

Comments and or exceptions: