



E321/E323 Print Cartridge
Printer: E321/E323

Declaration of Yield:	Average Cartridge Yield	3000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 3974
Std Dev 300
90% Lower Confidence 3818

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested **start** 16-Nov-2004 **stop** 17-Nov-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.2.2
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:	Cartridge	Printer	Temperature				Humidity			Cartridge Yield	Cartridge used in Calculation		
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg			Max	Min
	CAD041813512	8803YB4	74	23	74	23	74	23	49	49	48	4,034	Yes
	CAD041871287	8806BYY	74	23	74	23	74	23	49	49	48	4,312	Yes
	CAD041892222	8804PZB	74	23	74	23	74	23	49	49	48	3,395	Yes
	CAD041954704	8804R4B	74	23	74	23	74	23	49	49	48	3,777	Yes
	CAD041955058	8803YB4	74	23	74	23	74	23	48	49	48	4,209	Yes
	CAD041812170	8806BYY	74	23	74	23	74	23	48	49	48	4,241	Yes
	CAD041873150	8804PZB	74	23	74	23	74	23	48	49	48	3,929	Yes
	CAD041892252	8804R4B	74	23	74	23	74	23	48	49	48	3,927	Yes
	CAD041892569	8803YB4	74	23	74	23	74	23	48	49	48	4,097	Yes
	CAD041954961	8806BYY	74	23	74	23	74	23	48	49	48	4,168	Yes
	CAD041813270	8804PZB	74	23	74	23	74	23	48	49	48	4,155	Yes
	CAD041871009	8804R4B	74	23	74	23	74	23	48	49	48	3,443	Yes

Comments and or exceptions: