



**ISO/IEC 19752 Yield Test
Report**

Part Number: 24015SA,
24035SA

**E340-E342n Print Cartridge
Printer: E340-E342n**

see below for additional part
numbers

Declaration of Yield:	Average Cartridge Yield	2500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 3036
Std Dev 179
90% Lower Confidence 2944

For questions concerning testing

contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	14-Jul-2005	14-Jul-2005

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake 2nd shake
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	E340-E342n G10
Operating system	Windows 2000 Service Pack 4
Application software	Acrobat version 7.0.2
Test page version	19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:	Cartridge	Printer	Temperature				Humidity			Cartridge Yield	Cartridge used in Calculation		
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg			Max	Min
	CAC051740210	MDT2122	77	25	77	25	76	25	51	52	50	3080	Yes
	CAC051740207	MDT2091	77	25	77	25	76	25	51	52	50	3021	Yes
	CAC051740223	MDT2104	77	25	77	25	76	25	51	52	50	3151	Yes
	CAC051740222	MDT2161	77	25	77	25	76	25	51	52	50	3190	Yes
	CAC051740093	MDT2122	76	24	77	25	74	24	55	58	51	3141	Yes
	CAC051740094	MDT2091	76	24	77	25	74	24	55	58	51	3021	Yes
	CAC051740103	MDT2104	76	24	77	25	74	24	55	58	51	3211	Yes
	CAC051740100	MDT2161	76	24	77	25	74	24	55	58	51	3251	Yes
	CAC051740227	MDT2122	76	24	76	25	76	24	54	55	53	2620	Yes
	CAC051740095	MDT2091	76	24	76	25	76	24	54	55	53	2928	Yes
	CAC051740219	MDT2104	76	24	76	25	76	24	54	55	53	2848	Yes
	CAC051740228	MDT2161	76	24	76	25	76	24	54	55	53	2974	Yes

Comments and or exceptions:

Also covers:

12A8300	24018SL	34217HR
12A8400	24036SE	34237HR
24016SE	24037SR	SWE2500
24017SR	24038SL	