



ISO/IEC 19752 Yield Test Report

E352dn Ship With Equipment Print Cartridge

Printer: E352dn

Declaration of Yield:	Average Cartridge Yield	3000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 3644
Std Dev 144
90% Lower Confidence 3555

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 10-Jul-2006 **stop** 11-Jul-2006

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	E352dn G9
Operating system	Window XP
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS061531A8B	6203DDC	72	22	72	22	71	22	53	56	50	3,580	Yes
CAS061531A90	6203DD5	72	22	72	22	71	22	53	56	50	3,629	Yes
CAS061531AAB	6203DCP	72	22	72	22	71	22	53	56	50	3,411	Yes
CAS061531A87	6203DDC	73	23	73	23	72	22	55	56	54	3,809	Yes
CAS061531A97	6203DD5	73	23	73	23	72	22	55	56	54	3,790	Yes
CAS061531AC0	6203DCP	73	23	73	23	72	22	55	56	54	3,781	Yes
CAS061531A89	6203DDC	72	22	72	22	71	22	53	55	50	3,749	Yes
CAS061531A84	6203DD5	72	22	72	22	71	22	53	55	50	3,519	Yes
CAS061531A88	6203DCP	72	22	72	22	71	22	53	55	50	3,530	Yes

Comments and or exceptions: