



**ISO/IEC 19752 Yield Test
Report**

E460 3.5k Print Cartridge

Printer: E460

Declaration of Yield:	Average Cartridge Yield	3500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 4073
Std Dev 106
90% Lower Confidence 4008

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 6-Jun-2008 stop 9-Jun-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake No shake
Print mode	Continuous
Number of printers tested	3
Media used	Tidal Hammermill - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Long Bow Lexmark G9
Operating system	Windows XP SP2
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS081331A6A	Pluto	70	21	71	22	69	21	55	60	52	4,018	Yes
CAS081331A5A	Neptune	70	21	71	22	69	21	55	60	52	4,069	Yes
CAS081331A8B	Uranus	70	21	71	22	69	21	55	60	52	4,079	Yes
CAS081331A62	Neptune	71	22	72	22	69	21	54	56	50	4,079	Yes
CAS081331A4B	Pluto	71	22	72	22	69	21	54	56	50	3,939	Yes
CAS081331A88	Uranus	71	22	72	22	69	21	54	56	50	4,108	Yes
CAS081331A3A	Pluto	71	22	72	22	69	21	54	56	50	4,090	Yes
CAS081331A61	Neptune	71	22	72	22	69	21	54	56	50	3,969	Yes
CAS081331A69	Uranus	71	22	72	22	69	21	54	56	50	4,310	Yes

Comments and or exceptions: