

LEXMARK ISO/IEC 19752 Yield Test Report

E462 Extra High Yield Print Cartridge Printer E462

Declaration of Yield: **Average Cartridge Yield 18,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 18,708
Std Dev 805
90% Lower Confidence 18,209

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested start 7-Dec-2009 stop 15-Dec-2009

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure

1st shake At Toner Low
2nd shake At Fade

Print mode Continuous
Number of printers tested 3
Media used Hammermill Tidal - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version E462 G4
Operating system Windows XP2
Application software Acrobat version 7.1.0
Test page version 19752 Test Chart.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
CAA093077FF8	72H67D7	74 / 23	78 / 26	71 / 22	48	51	46	18,961	Y
CAA093077FFB	72H67DB	74 / 23	78 / 26	71 / 22	48	51	46	18,357	Y
CAA093078000	72H67CZ	74 / 23	78 / 26	71 / 22	48	51	46	18,393	Y
CAA093077FE5	72H67D7	72 / 22	74 / 23	71 / 22	49	53	47	17,950	Y
CAA09307800C	72H67DB	72 / 22	74 / 23	71 / 22	49	53	47	17,970	Y
CAA093077FF2	72H67CZ	72 / 22	74 / 23	71 / 22	49	53	47	19,410	Y
CAA093078012	72H67D7	72 / 22	74 / 23	71 / 22	50	53	47	19,500	Y
CAA093077FFC	72H67DB	72 / 22	74 / 23	71 / 22	50	53	47	17,780	Y
CAA093077FEZ	72H67CZ	72 / 22	74 / 23	71 / 22	50	53	47	20,050	Y

Comments and or exceptions: