

LEXMARK TM ISO/IEC 19752 Yield Test Report

MS410 Extra High Yield Print Cartridge Printer MS410

Declaration of Yield:

Average Cartridge Yield	10,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 12,399
Std Dev 696
90% Lower Confidence 11,967

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	19-Apr-2012	23-Apr-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series (G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS1205869AE	4514PTB300139	71	76	70	55	63	48	13,425	Y	
(S)CAS120586A3A	4514PTB300139	71	76	70	55	63	48	12,383	Y	
(S)CAS120586913	4514PTB300139	71	76	70	55	63	48	11,886	Y	
(S)CAS1205869F8	4514PTB300117	71	76	70	55	63	48	12,455	Y	
(S)CAS1205869A6	4514PTB300117	71	76	70	55	63	48	11,896	Y	
(S)CAS1205869FA	4514PTB300117	71	76	70	55	63	48	11,492	Y	
(S)CAS1205869B3	4514PTB300145	71	76	70	55	63	48	13,564	Y	
(S)CAS1205869A5	4514PTB300145	71	76	70	55	63	48	12,442	Y	
(S)CAS120586A0C	4514PTB300145	71	76	70	55	63	48	12,046	Y	

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.