



ISO/IEC 19752 Yield Test Report

MS610 Print Cartridge Printer MS610

Declaration of Yield:

Average Cartridge Yield	1,500	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 2,642
Std Dev 339
90% Lower Confidence 2,432

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	start	stop
Date Tested	7-May-2012	8-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series(G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS1205970B9	4514PTB300198	4514PTB300198	71	75	69	50	53	43	3,030	Y
(S)CAS1205970BB	4514PTB300198	4514PTB300198	71	75	69	50	53	43	2,529	Y
(S)CAS120597092	4514PTB300198	4514PTB300198	71	75	69	50	53	43	2,380	Y
(S)CAS1205970CB	4514PTB300207	4514PTB300207	71	75	69	50	53	43	2,409	Y
(S)CAS1205970D7	4514PTB300207	4514PTB300207	71	75	69	50	53	43	2,875	Y
(S)CAS1205970D8	4514PTB300207	4514PTB300207	71	75	69	50	53	43	2,540	Y
(S)CAS1205970A1	4514PTB300611	4514PTB300611	71	75	69	50	53	43	3,181	Y
(S)CAS12059709C	4514PTB300611	4514PTB300611	71	75	69	50	53	43	2,710	Y
(S)CAS1205970A0	4514PTB300611	4514PTB300611	71	75	69	50	53	43	2,121	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.