



ISO/IEC 19752 Yield Test Report

MS610 Extra High Yield Print Cartridge Printer MS610

Declaration of Yield:	Average Cartridge Yield	20,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 21,881
Std Dev 1,150
90% Lower Confidence 21,168

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 18-May-2012	<u>stop</u> 24-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series (G3)
Operating system		Windows XP SP3
Application software		Adobe Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120586A18	4514PTB300198	75	78	68	42	50	38	22,960	Y
(S)CAS120586A1A	4514PTB300198	75	78	68	42	50	38	22,381	Y
(S)CAS120586A1C	4514PTB300198	75	78	68	42	50	38	20,172	Y
(S)CAS1205869AB	4514PTB300207	75	78	68	42	50	38	23,210	Y
(S)CAS1205869B7	4514PTB300207	75	78	68	42	50	38	21,383	Y
(S)CAS120586A1B	4514PTB300207	75	78	68	42	50	38	20,922	Y
(S)CAS1205869D3	4514PTB300608	75	78	68	42	50	38	21,900	Y
(S)CAS1205869D1	4514PTB300608	75	78	68	42	50	38	20,718	Y
(S)CAS1205869AA	4514PTB300608	75	78	68	42	50	38	23,279	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.