

LEXMARK TM ISO/IEC 19752 Yield Test Report

MS710 Print Cartridge Printer MS710

Declaration of Yield: **Average Cartridge Yield 6,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 7,514
Std Dev 189
90% Lower Confidence 7,397

For questions concerning testing contact
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	10-Sep-2012	12-Sep-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 11
Operating system		Windows XP SP3
Application software		Acrobat version 9.0
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS122383C5B	406322990000T	72	74	69	52	56	49	7,599	Y
(S)CAS122383C68	406322990000T	72	74	69	52	56	49	7,683	Y
(S)CAS122383C6B	406322990000T	72	74	69	52	56	49	7,540	Y
(S)CAS122383C5A	4063229900009	72	74	69	52	56	49	7,318	Y
(S)CAS122383C69	4063229900009	72	74	69	52	56	49	7,266	Y
(S)CAS122383C5D	4063229900009	72	74	69	52	56	49	7,408	Y
(S)CAS122383C6E	4063229900007	72	74	69	52	56	49	7,879	Y
(S)CAS122383C57	4063229900007	72	74	69	52	56	49	7,475	Y
(S)CAS122383C6D	4063229900007	72	74	69	52	56	49	7,461	Y

Comments and or exceptions:

*EOL was determined by the printer calling for the cartridge to be replaced.