

LEXMARK ISO/IEC 19752 Yield Test Report

MS711 Print Cartridge Printer MS711

Declaration of Yield:

Average Cartridge Yield	6,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 7,511
Std Dev 145
90% Lower Confidence 7,421

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	start 10-Sep-2012	stop 12-Sep-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 11
Operating system		Windows XP SP3
Application software		Acrobat version 9.0
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
Cartridge	Printer								
(S)CAS122383C61	406322990000T	72	74	69	52	56	49	7,599	Y
(S)CAS122383C76	406322990000T	72	74	69	52	56	49	7,683	Y
(S)CAS122383C74	406322990000T	72	74	69	52	56	49	7,540	Y
(S)CAS122383C72	4063229900009	72	74	69	52	56	49	7,318	Y
(S)CAS122383C6F	4063229900009	72	74	69	52	56	49	7,266	Y
(S)CAS122383C54	4063229900009	72	74	69	52	56	49	7,408	Y
(S)CAS122383C63	4063229900007	72	74	69	52	56	49	7,879	Y
(S)CAS122383C5E	4063229900007	72	74	69	52	56	49	7,475	Y
(S)CAS122383C62	4063229900007	72	74	69	52	56	49	7,461	Y

Comments and or exceptions:

*EOL was determined by the printer calling for the cartridge to be replaced.