

LEXMARK ISO/IEC 19752 Yield Test Report

MX811 Print Cartridge Printer MX811

Declaration of Yield: **Average Cartridge Yield 10,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 11,076
Std Dev 483
90% Lower Confidence 10,776

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	start	stop
Date Tested	4-May-2012	6-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120545DDF	406312790000Z	74	78	69	40	48	37	10,885	Y
(S)CAS120545DE8	406312790000Z	74	78	69	40	48	37	10,380	Y
(S)CAS120545DE0	406312790000Z	74	78	69	40	48	37	10,720	Y
(S)CAS120545DEE	406312790000Y	74	78	69	40	48	37	11,090	Y
(S)CAS120545DEC	406312790000Y	74	78	69	40	48	37	10,700	Y
(S)CAS120545DF2	406312790000Y	74	78	69	40	48	37	10,960	Y
(S)CAS120545DFF	40631279000085	74	78	69	40	48	37	11,800	Y
(S)CAS120545DEA	40631279000085	74	78	69	40	48	37	11,425	Y
(S)CAS120545DD8	40631279000085	74	78	69	40	48	37	11,720	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.