



## ISO/IEC 19752 Yield Test Report

### MS811 Print Cartridge

Printer MS811

Declaration of Yield:	<b>Average Cartridge Yield    6,000    Standard Pages</b> <b>Declared yield in accordance with ISO/IEC 19752</b>
-----------------------	---

**Average 6,777**  
**Std Dev 322**  
**90% Lower Confidence 6,577**

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
<b>Date Tested</b>	7-May-2012	8-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120545DF4	406312790000Z	73	78	69	41	48	37	6,546	Y	
(S)CAS120545E16	406312790000Z	73	78	69	41	48	37	6,350	Y	
(S)CAS120545DFC	406312790000Z	73	78	69	41	48	37	6,703	Y	
(S)CAS120545E1B	406312790000Y	73	78	69	41	48	37	6,592	Y	
(S)CAS120545E15	406312790000Y	73	78	69	41	48	37	6,856	Y	
(S)CAS120545DF3	406312790000Y	73	78	69	41	48	37	6,493	Y	
(S)CAS120545E0B	4063127900085	73	78	69	41	48	37	6,988	Y	
(S)CAS120545E19	4063127900085	73	78	69	41	48	37	7,174	Y	
(S)CAS120545DFE	4063127900085	73	78	69	41	48	37	7,292	Y	

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.