



ISO/IEC 19752 Yield Test Report

MS812 Print Cartridge

Printer MS812

Declaration of Yield:	Average Cartridge Yield 6,000 Standard Pages Declared yield in accordance with ISO/IEC 19752
-----------------------	---

Average 6,436
Std Dev 136
90% Lower Confidence 6,351

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	7-May-2012	8-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120545E1C	40631279000BB	40631279000BB	73	78	69	41	48	37	6,223	Y
(S)CAS120545E1D	40631279000BB	40631279000BB	73	78	69	41	48	37	6,414	Y
(S)CAS120545E20	40631279000BB	40631279000BB	73	78	69	41	48	37	6,497	Y
(S)CAS120545E18	4063127900043	4063127900043	73	78	69	41	48	37	6,509	Y
(S)CAS120555B9A	4063127900043	4063127900043	73	78	69	41	48	37	6,707	Y
(S)CAS120545E3A	4063127900043	4063127900043	73	78	69	41	48	37	6,449	Y
(S)CAS120545E1F	406312790004K	406312790004K	73	78	69	41	48	37	6,438	Y
(S)CAS120545E23	406312790004K	406312790004K	73	78	69	41	48	37	6,307	Y
(S)CAS120545E21	406312790004K	406312790004K	73	78	69	41	48	37	6,376	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.