



ISO/IEC 19752 Yield Test Report
MX410 High Yield Print Cartridge
 Printer MX410

Declaration of Yield:

Average Cartridge Yield	10,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 12,371
Std Dev 670
90% Lower Confidence 11,955

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	19-Apr-2012	30-Apr-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120586A3B	4514PTB300302	71	76	70	53	62	45	12,780	Y	
(S)CAS120586A3C	4514PTB300302	71	76	70	53	62	45	13,542	Y	
(S)CAS1205869FD	4514PTB300302	71	76	70	53	62	45	12,434	Y	
(S)CAS120586A2C	4514PTB300307	71	76	70	53	62	45	13,125	Y	
(S)CAS12058693B	4514PTB300307	71	76	70	53	62	45	12,268	Y	
(S)CAS1205869FB	4514PTB300307	71	76	70	53	62	45	11,732	Y	
(S)CAS1205869DB	4514PTB300326	71	73	70	46	54	43	12,077	Y	
(S)CAS1205869D7	4514PTB300326	71	73	70	46	54	43	11,846	Y	
(S)CAS1205869D6	4514PTB300326	71	73	70	46	54	43	11,532	Y	

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.