



ISO/IEC 19752 Yield Test Report

MX61X Print Cartridge

Printer MX610 / MX611

Declaration of Yield:	Average Cartridge Yield 2,500 Standard Pages Declared yield in accordance with ISO/IEC 19752
-----------------------	---

Average 3,543
Std Dev 125
90% Lower Confidence 3,465

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	3-May-2012	4-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120586FD5	4514PTB300207	4514PTB300207	71	72	69	53	58	50	3,506	Y
(S)CAS120586F6D	4514PTB300207	4514PTB300207	71	72	69	53	58	50	3,500	Y
(S)CAS120586FDC	4514PTB300207	4514PTB300207	71	72	69	53	58	50	3,379	Y
(S)CAS1205970F5	4514PTB300205	4514PTB300205	71	72	69	53	58	50	3,727	Y
(S)CAS120586F91	4514PTB300205	4514PTB300205	71	72	69	53	58	50	3,588	Y
(S)CAS120586FDD	4514PTB300205	4514PTB300205	71	72	69	53	58	50	3,621	Y
(S)CAS1205970F4	4514PTB300198	4514PTB300198	71	72	69	53	58	50	3,679	Y
(S)CAS120586F6E	4514PTB300198	4514PTB300198	71	72	69	53	58	50	3,360	Y
(S)CAS120586F99	4514PTB300198	4514PTB300198	71	72	69	53	58	50	3,524	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.