

LEXMARK ISO/IEC 19752 Yield Test Report

MX810 High Yield Print Cartridge Printer MX810

Declaration of Yield:

Average Cartridge Yield	25,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 30,520
Std Dev 1,792
90% Lower Confidence 29,409

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	19-Jul-2012	9-Aug-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
Cartridge	Printer								
(S)CAS1219231FC	4063127900002	71	75	68	48	55	43	31,971	Y
(S)CAS1219231D1	4063127900002	71	75	68	48	55	43	32,168	Y
(S)CAS1219231DF	4063127900002	71	75	68	48	55	43	30,673	Y
(S)CAS1219231F2	4063127900005	71	75	68	48	55	43	31,962	Y
(S)CAS1219231FA	4063127900005	71	75	68	48	55	43	32,053	Y
(S)CAS1219231E0	4063127900005	71	75	68	48	55	43	31,189	Y
(S)CAS1219231F4	4063127900010	71	75	68	48	55	43	28,003	Y
(S)CAS1219231CC	4063127900010	71	75	68	48	55	43	28,183	Y
(S)CAS1219231B8	4063127900010	71	75	68	48	55	43	28,477	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.