

**T430 Print Cartridge**

Printer: T430

Declaration of Yield: **Average Cartridge Yield 6000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

**Average** 7323  
**Std Dev** 327  
**90% Lower Confidence** 7179

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**start stop**  
**Date tested** 24-Jun-2004 7-Jul-2004

Number of cartridges in testing 16  
 Qty. of cartridges used in calculation 16  
 Shake Procedure 1st shake At fade  
 2nd shake At fade  
 Print mode Continuous  
 Number of printers tested 4  
 Media used Boise Cascade X9 - 20# - Letter  
 Paper feed orientation Short Edge Feed (SEF)  
 Driver version T430 G9  
 Operating system Windows 98  
 Application software Acrobat version 6.01  
 Test page version Standard\_Testpage\_(PDF\_1.3).pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAD041313843	792000W	73	74	71	51	54	49	7,857	Y
CAD041313900	792000T	73	74	71	51	54	49	7,554	Y
CAD041313901	7920001	73	74	71	51	54	49	7,308	Y
CAD041313937	792000M	73	74	71	51	54	49	7,222	Y
CAD041313861	792000W	75	77	72	50	53	49	7,328	Y
CAD041313879	792000T	75	77	72	50	53	49	7,126	Y
CAD041313909	7920001	75	77	72	50	53	49	7,653	Y
CAD041313925	792000M	75	77	72	50	53	49	7,528	Y
CAD041313873	792000W	75	77	72	50	53	46	7,587	Y
CAD041313870	792000T	75	77	72	50	53	46	7,291	Y
CAD041313850	7920001	75	77	72	50	53	46	6,889	Y
CAD041313855	792000M	75	77	72	50	53	46	6,477	Y
CAD041313874	792000W	74	77	71	51	52	48	7,153	Y
CAD041313898	792000T	74	77	71	51	52	48	7,505	Y
CAD041313920	7920001	74	77	71	51	52	48	7,217	Y
CAD041313882	792000M	74	77	71	51	52	48	7,465	Y

Comments and or exceptions: