



T520/T522 High Yield Print Cartridge
Printer: T522

Declaration of Yield: **Average Cartridge Yield 20000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 21469
Std Dev 466
90% Lower Confidence 21227

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 17-Jan-2005 stop 21-Jan-2005

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake At toner low
2nd shake At toner low
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 7.4.1
Operating system Windows 2000
Application software Adobe Acrobat version 5
Test page version Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAX043501FD5D	9903G65	74	24	75	24	74	23	48	51	48	20,709	Yes
CAX043501FDBD	E004876	74	24	75	24	74	23	48	51	48	21,168	Yes
CAX043510E10D	E004877	74	24	75	24	74	23	48	51	48	21,229	Yes
CAX04351085FD	E004915	74	24	75	24	74	23	48	51	48	21,110	Yes
CAX0435108ABD	9903G65	74	24	75	24	74	23	48	49	48	21,397	Yes
CAX0435204BDD	E004876	74	24	75	24	74	23	48	49	48	21,238	Yes
CAX0435204BAD	E004877	74	24	75	24	74	23	48	49	48	22,452	Yes
CAX0435108A1D	E004915	74	24	75	24	74	23	48	49	48	21,318	Yes
CAX0435204B8D	9903G65	74	24	75	24	74	23	48	49	48	21,844	Yes
CAX0435109ABD	E004876	74	24	75	24	74	23	48	49	48	21,752	Yes
CAX043501FCDD	E004877	74	24	75	24	74	23	48	49	48	21,980	Yes
CAX043501FDCD	E004915	74	24	75	24	74	23	48	49	48	21,426	Yes

Comments and or exceptions: