



T520/T522 Print Cartridge

Printer:

Declaration of Yield:	Average Cartridge Yield	7500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 8040
Std Dev 365
90% Lower Confidence 7851

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested **start** 29-Oct-2004 **stop** 31-Oct-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 5
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:	Cartridge	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS041330258	9903G65	74	23	75	24	74	23	48	49	48	8,384	Yes	
CAX041744901	E004876	74	23	75	24	74	23	48	49	48	7,969	Yes	
CAS041402030	E004877	74	23	75	24	74	23	48	49	48	7,687	Yes	
CAS041530965	E004915	74	23	75	24	74	23	48	49	48	7,925	Yes	
CAX041745867	9903G65	74	23	74	24	74	23	48	48	48	7,806	Yes	
CAS041530949	E004876	74	23	74	24	74	23	48	48	48	7,615	Yes	
CAS041330245	E004877	74	23	74	24	74	23	48	48	48	8,762	Yes	
CAS041402027	E004915	74	23	74	24	74	23	48	48	48	8,001	Yes	
CAS041530944	9903G65	74	23	75	24	74	23	48	48	48	7,702	Yes	
CAS041402008	E004876	74	23	75	24	74	23	48	48	48	7,843	Yes	
CAX041744109	E004877	74	23	75	24	74	23	48	48	48	8,240	Yes	
CAS041330225	E004915	74	23	75	24	74	23	48	48	48	8,546	Yes	

Comments and or exceptions: