



T620/T622 High Yield Print Cartridge
Printer: T620

Declaration of Yield: Average Cartridge Yield 30000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average 34126
Std Dev 1186
90% Lower Confidence 33511

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 19-Jan-2005 stop 27-Jan-2005

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake 2nd shake
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 7.4.1
Operating system Windows 2000
Application software Adobe Acrobat version 5
Test page version Standard\_Testpage\_(PDF\_1.3).pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Rows include various cartridge models like CAX043500FEC, CAX043501D06, etc.

Comments and or exceptions: