



T620/T622 High Yield Print Cartridge
Printer: T622

Declaration of Yield: **Average Cartridge Yield 30000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 34943
Std Dev 1913
90% Lower Confidence 33951

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 19-Jan-2005 stop 27-Jan-2005

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake At toner low
2nd shake At toner low
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 7.4.1
Operating system Windows 2000
Application software Adobe Acrobat version 5
Test page version Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAX043500ED8	N5780150	74	24	75	24	74	23	48	49	48	35,101	Yes
CAX043500EE2	41MF623	74	24	75	24	74	23	48	49	48	32,942	Yes
CAX043511B28	41ZT414	74	24	75	24	74	23	48	49	48	34,534	Yes
CAX0435204C1	41ZT513	74	24	75	24	74	23	48	49	48	33,626	Yes
CAX043510E58	N5780150	74	24	75	24	74	23	48	49	48	37,550	Yes
CAX043511B29	41MF623	74	24	75	24	74	23	48	49	48	33,994	Yes
CAX0435204C2	41ZT414	74	24	75	24	74	23	48	49	48	32,202	Yes
CAX043510E5F	41ZT513	74	24	75	24	74	23	48	49	48	37,125	Yes
CAX043500FE8	N5780150	74	24	75	24	74	23	48	49	48	38,358	Yes
CAX043510E55	41MF623	74	24	75	24	74	23	48	49	48	33,371	Yes
CAX043500FE9	41ZT414	74	24	75	24	74	23	48	49	48	35,197	Yes
CAX0435022F9	41ZT513	74	24	75	24	74	23	48	49	48	35,313	Yes

Comments and or exceptions: