



T630, T632, T634 Print Cartridge

Printer: T630

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>5000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 6109  
**Std Dev** 412  
**90% Lower Confidence** 5895

**For questions concerning testing contact:**

Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

**Date tested**      **start** 28-Sep-2004      **stop** 29-Sep-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.4.0.0
Operating system	Windows 2000
Application software	Adobe Acrobat version 5.0
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:	Cartridge	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
	CAX042029550D	991G23K	75	24	75	24	74	24	51	52	51	5,380	Yes
	CAX042066319D	991G3TC	75	24	75	24	74	24	51	52	51	6,430	Yes
	CAX041658921D	991G3T3	75	24	75	24	74	24	51	52	51	5,974	Yes
	CAX041630112D	991G23X	75	24	75	24	74	24	51	52	51	6,334	Yes
	CAX041638438D	991G23K	75	24	75	24	75	24	51	51	51	5,910	Yes
	CAX042029562D	991G3TC	75	24	75	24	75	24	51	51	51	5,497	Yes
	CAX042066299D	991G3T3	75	24	75	24	75	24	51	51	51	6,269	Yes
	CAX041658058D	991G23X	75	24	75	24	75	24	51	51	51	6,036	Yes
	CAX041658910D	991G23K	74	23	75	24	74	23	51	52	51	5,992	Yes
	CAX041637876D	991G3TC	74	23	75	24	74	23	51	52	51	6,619	Yes
	CAX042029571D	991G3T3	74	23	75	24	74	23	51	52	51	6,776	Yes
	CAX042066264D	991G23X	74	23	75	24	74	23	51	52	51	6,088	Yes

Comments and or exceptions: