



T630, T632, T634 High Yield Print Cartridge
Printer: T634

Declaration of **Average Cartridge Yield 21000 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 22180
Std Dev 1020
90% Lower Confidence 21651

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 29-Sep-2004 stop 2-Oct-2004

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake At toner low
2nd shake At toner low
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 8.4.0.0
Operating system Windows 2000
Application software Adobe Acrobat version 5.0
Test page version Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAC042260247	9914W10	74	24	75	24	74	23	51	52	51	22,107	Yes
CAX041613011	9914W1H	74	24	75	24	74	23	51	52	51	21,784	Yes
CAX042239713	9914W5W	74	24	75	24	74	23	51	52	51	22,385	Yes
CAC042290766	9914W6Y	74	24	75	24	74	23	51	52	51	19,713	Yes
CAC042290742	9914W10	75	24	75	24	74	24	51	52	51	22,812	Yes
CAC042260238	9914W1H	75	24	75	24	74	24	51	52	51	22,216	Yes
CAX041614164	9914W5W	75	24	75	24	74	24	51	52	51	22,237	Yes
CAX042238878	9914W6Y	75	24	75	24	74	24	51	52	51	23,404	Yes
CAX042239718	9914W10	74	23	75	24	74	23	51	52	51	23,164	Yes
CAC042290745	9914W1H	74	23	75	24	74	23	51	52	51	21,477	Yes
CAC042260258	9914W5W	74	23	75	24	74	23	51	52	51	21,519	Yes
CAX041611359	9914W6Y	74	23	75	24	74	23	51	52	51	23,346	Yes

Comments and or exceptions: