



**ISO/IEC 19752 Yield Test  
Report**

T650, T652, T654 High Yield Print Cartridge

Printer: T652

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>25000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 27643  
**Std Dev** 504  
**90% Lower Confidence** 27330

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested** start 7-Aug-2008 stop 11-Aug-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS081432214	PLT1042	71	21	72	22	69	21	56	58	52	27,405	Yes
CAS08143224A	PLT1042	71	22	73	23	71	21	53	54	50	28,199	Yes
CAS081432217	PLT1042	72	22	72	22	71	22	50	53	49	27,328	Yes
CAS08143222C	PLT1051	71	21	71	22	69	21	56	58	54	28,235	Yes
CAS08143222D	PLT1051	71	22	73	23	71	21	53	54	51	26,768	Yes
CAS0814321F7	PLT1051	72	22	73	23	73	23	50	51	51	28,169	Yes
CAS08143222F	PLT1040	71	21	72	22	69	21	56	58	53	27,742	Yes
CAS08143222A	PLT1040	71	22	73	23	71	21	53	54	51	27,237	Yes
CAS081432204	PLT1040	72	22	73	23	70	21	50	53	48	27,701	Yes

**Comments and or exceptions:**