



**ISO/IEC 19752 Yield Test Report**

T654 Extra High Yield Print Cartridge

Printer: T654

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>36000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 39584  
**Std Dev** 1005  
**90% Lower Confidence** 38961

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      **start** 29-Jul-2008      **stop** 31-Jul-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
		Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS081432161	PLT1112	72	22	73	23	69	21	58	63	56	39,894	Yes
CAS081432177	PLT1112	72	22	73	23	70	21	59	62	56	39,219	Yes
CAS081432162	PLT1112	72	22	73	23	71	22	58	59	56	38,700	Yes
CAS081432145	PLT1118	72	22	73	23	71	22	58	59	56	38,734	Yes
CAS081432169	PLT1118	72	22	73	23	70	21	59	62	56	39,050	Yes
CAS08143217E	PLT1118	72	22	73	23	71	22	58	60	57	39,669	Yes
CAS081432164	PLT1072	72	22	73	23	69	21	58	63	56	39,356	Yes
CAS081432174	PLT1072	72	22	73	23	70	21	59	62	56	42,035	Yes
CAS081432162	PLT1072	72	22	73	23	71	22	58	60	57	39,598	Yes

**Comments and or exceptions:**