



W812 Print Cartridge

Printer: W812

Declaration of Yield:	Average Cartridge Yield	12000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 14410
Std Dev 1405
90% Lower Confidence 13539

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 27-Sep-2004 **stop** 29-Sep-2004

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Long Edge Feed (LEF)
Driver version	W812 Printer Driver 8.0.1
Operating system	Windows 2000 SP4
Application software	Acrobat Reader Version 6.0.2
Test page version	IS_19752_Testpage.pdf

Cartridge testing data:	Cartridge	Printer	Temperature				Humidity			Cartridge Yield	Cartridge used in Calculation		
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg			Max	Min
	ACT350172A044620047130	02-11162	72	22	74	23	70	21	51	57	48	13,380	Yes
	ACT350172A044220047130	02-10641	72	22	74	23	70	21	51	57	48	14,520	Yes
	ACT350172A045220047130	02-10726	72	22	74	23	70	21	51	57	48	13,810	Yes
	ACT350172A098320035080	02-11162	74	23	76	25	72	22	49	53	44	14,000	Yes
	ACT350172A045120047130	02-10726	74	23	76	25	72	22	49	53	44	13,540	Yes
	ACT350172A098420035080	02-10641	74	23	76	25	72	22	49	53	44	17,980	Yes
	ACT350172A031720047130	02-11162	75	24	76	24	75	24	47	49	44	13,860	Yes
	ACT350172A038520047130	02-10641	75	24	76	24	75	24	47	49	44	14,720	Yes
	ACT350172A039720047130	02-10726	75	24	76	24	75	24	47	49	44	13,880	Yes

Comments and or exceptions: