



**ISO/IEC 19752 Yield Test Report**

Part Number: W84020H

**W840 Print Cartridge**

Printer: W840

Declaration of Yield: **Average Cartridge Yield 30000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

**Average** 35086  
**Std Dev** 1852  
**90% Lower Confidence** 33938

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested** start 2-May-2005 stop 5-May-2005

Number of cartridges in testing 9  
 Qty. of cartridges used in calculation 9  
 Shake Procedure 1st shake No shake  
 2nd shake No shake  
 Print mode Continuous  
 Number of printers tested 3  
 Media used Boise Cascade - 20# - Letter  
 Paper feed orientation Long Edge Feed (LEF)  
 Driver version W840 PCL-XL G4  
 Operating system Windows XP SP2  
 Application software Adobe Acrobat Professional 6.0.2  
 Test page version Download\_Free\_\_\_19752\_Test\_Chart\_Ver.200406\_.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
JP-CT200435-54L-1001000587	ML	75	24	76	24	74	23	47	48	45	34,900	Yes
JP-CT200435-54L-1001000579	LF	75	24	76	24	74	23	47	48	45	33,770	Yes
JP-CT200435-54L-1001000581	LS	75	24	76	24	74	23	47	48	45	35,990	Yes
JP-CT200435-54L-1001000586	ML	74	24	75	24	74	23	48	49	46	37,370	Yes
JP-CT200435-54L-1001000517	LF	74	24	75	24	74	23	48	49	46	36,510	Yes
JP-CT200435-54L-1001000583	LS	74	24	75	24	74	23	48	49	46	37,530	Yes
JP-CT200435-54L-1001000521	ML	75	24	75	24	74	23	47	48	46	33,850	Yes
JP-CT200435-54L-1001000520	LF	75	24	75	24	74	23	47	48	46	33,540	Yes
JP-CT200435-54L-1001000523	LS	75	24	75	24	74	23	47	48	46	32,310	Yes

**Comments and or exceptions:**

Test ran between Toner Lows with pages removed for Fade.