



X340 Ship With Equipment Print Cartridge

Printer: X340

Declaration of Yield:	Average Cartridge Yield	1500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 3030
Std Dev 241
90% Lower Confidence 2881

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	start	stop
Date tested	2-Mar-2006	3-Mar-2006

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	X340 XI G2
Operating system	Windows XP
Application software	Acrobat version 7.01
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS0526240A1C	YIELD-1	74	23	74	23	74	23	45	48	45	3301	Yes
CAS0526240A19	YIELD-2	74	23	74	23	74	23	45	48	45	2942	Yes
CAS0526240A23	YIELD-3	74	23	74	23	74	23	45	48	45	3121	Yes
CAS0526240A04	YIELD-1	74	23	74	24	74	23	42	43	40	3301	Yes
CAS0526240C6B	YIELD-2	74	23	74	24	74	23	42	43	40	3151	Yes
CAS0526240A1D	YIELD-3	74	23	74	24	74	23	42	43	40	2751	Yes
CAS0526240A28	YIELD-1	74	23	74	23	74	23	45	46	44	2769	Yes
CAS0526240C6D	YIELD-2	74	23	74	23	74	23	45	46	44	2710	Yes
CAS0526240A22	YIELD-3	74	23	74	23	74	23	45	46	44	3222	Yes

Comments and or exceptions: