



ISO/IEC 19752 Yield Test Report

X651, X652, X654, X656, X658 High Yield Print Cartridge

Printer: X651, X652

Declaration of Yield:	Average Cartridge Yield	25000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 28566
Std Dev 506
90% Lower Confidence 28253

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 18-Aug-2008 **stop** 20-Aug-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	X65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS0814322DB	PLT1125	72	22	73	23	70	21	49	52	47	28,819	Yes
CAS0814322D1	PLT1125	70	21	72	22	68	20	53	56	49	27,586	Yes
CAS0814322E1	PLT1125	71	21	72	22	68	20	54	59	50	28,538	Yes
CAS0814322EA	PLT1105	72	22	73	23	70	21	49	52	47	27,994	Yes
CAS0814322F5	PLT1105	70	21	72	22	68	20	53	56	50	28,687	Yes
CAS0814322E8	PLT1105	71	21	72	22	69	20	54	59	50	28,988	Yes
CAS0814322E4	PLT1112	72	22	73	23	70	21	49	52	47	29,146	Yes
CAS0814322C7	PLT1112	70	21	72	22	68	20	52	56	50	28,940	Yes
CAS0814322CE	PLT1112	71	21	72	22	69	20	54	59	52	28,400	Yes

Comments and or exceptions: