



# ISO/IEC 19752 Yield Test Report

X830e/X832e Print Cartridge

Printer: X830e

Part Numbers: X8302KH

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>30000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 33157  
**Std Dev** 906  
**90% Lower Confidence** 32596

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested** start 8-Jun-2004 stop 14-Jun-2004

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade X-9000 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	W820 Driver Version 7.4.1
Operating system	Windows 2000 SP4
Application software	Acrobat version 6.01
Test page version	Standard_Testpage_(19752_2004).pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
J0-80507-4517K30	01-65579	74	23	74	23	73	23	58	60	57	34,014	Yes
J0-80509-4517K30	01-65601	74	23	74	23	73	23	58	60	57	33,074	Yes
J0-80510-4517K30	01-52970	74	23	74	23	73	23	58	60	57	32,494	Yes
J0-80505-4517K30	01-65579	74	23	75	24	73	23	58	61	57	32,730	Yes
J0-80512-4517K30	01-65601	74	23	75	24	73	23	58	61	57	32,330	Yes
J0-80508-4517K30	01-52970	74	23	75	24	73	23	58	61	57	31,931	Yes
J3-80782-4423K30	01-65579	73	23	74	23	72	22	60	63	59	34,451	Yes
J3-80773-4423K30	01-65601	73	23	74	23	72	22	60	63	59	34,311	Yes
J3-80803-4423K30	01-52970	73	23	74	23	72	22	60	63	59	33,081	Yes

Comments and or exceptions: